Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capacing the first texture in the consumption will depend on how the appliance is used. Rated capacing the first texture in the consumption will depend on how the appliance is used. Programme depend on the consumption will depend on how the appliance is used. Programme temperature inside the treated textile ^(a) (°C) Rated capacing the first texture in the consumption will depend on how the appliance is used. Programme depend on the capacing texture in the consumption will depend on how the appliance is used. Rated capacing the first texture in the capacing texture	8.0 51.7 .033		Miele Carl-Miele-Straße 29, 33332 Güter WWD020 WCS 8kg Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a)	Value Height Width Depth	85 60	
Model identifier General product parameters Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capacing that the treated textile ^(a) (°C) Spin speed ^(a) (rpm) Half Quarter Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	8.0 51.7 .033		Parameter Dimensions in cm Energy efficiency class ^(a)	Value Height Width Depth		
Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	8.0 51.7 .033		Parameter Dimensions in cm Energy efficiency class ^(a)	Height Width Depth		
Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	8.0 51.7 .033		Dimensions in cm Energy efficiency class ^(a)	Height Width Depth		
Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	8.0 51.7 .033		Dimensions in cm Energy efficiency class ^(a)	Height Width Depth		
Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	51.7		Energy efficiency class ^(a)	Width Depth		
Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	51.7		Energy efficiency class ^(a)	Depth	60	
Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	.033		,			
Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	.033		,	Α	64	
Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration(a) (h:min) Half Quarter Airborne acoustical noise emission class(a) (spinning phase)			Rinsing effectiveness (g/kg) ^(a)	Α		
kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C) Rated capace Half Quarter Rated capace Rated capace Programme duration(a) (h:min) Half Quarter Airborne acoustical noise emission class(a) (spinning phase)	.470		11 11	4.0		
Maximum temperature inside the treated textile ^(a) (°C) Quarter	0.470		Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water.	47		
the treated textile ^(a) (°C) Quarter Rated capace Spin speed ^(a) (rpm) Half Quarter Rated capace Airborne acoustical noise emission class ^(a) (spinning phase)	Rated capacity 41 Half 30		Weighted remaining moisture content ^(a) (%)	51.0		
Spin speed ^(a) (rpm) Half Quarter Rated capace Rated c						
Spin speed ^(a) (rpm) Half Quarter Rated capace Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)		25				
Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	ity	1400				
Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)	Half 1400		Spin-drying efficiency class ^(a)	В		
Programme duration ^(a) (h:min) Half Quarter Airborne acoustical noise emission class ^(a) (spinning phase)		1400				
Airborne acoustical noise emission class ^(a) (spinning phase)	ity	3:39				
Airborne acoustical noise emission class ^(a) (spinning phase)	Half 2:47		Design type	Free-standing		
emission class ^(a) (spinning phase)		2:47				
Off-mode (W) (if applicable)	72		Airborne acoustical noise emission class ^(a) (spinning phase)	А		
	0.30		Standby mode (W) (if applicable)	-		
Delay start (W) (if applicable)	3.80		Networked standby (W) (if applicable)	-		
Minimum duration of the guarantee offered by	ວy the sເ	upplier	24 months			
This product has been designed to release silv	ver ions	during	no			
Additional information				•		
Weblink to the supplier's website, where the inf 9 of Annex II to Commission Regulation (EU) 2 found		•	https://www.miele.com/			