

Attachment 4: Product information sheet

No.	Parameter	Parameter value and precision			Unit
1.	Supplier's name or trade mark	ADX			TEXT
	Supplier's address	31/F AXA Tower Landmark East, 100 How Ming Street, Kwun Tong, Kowloon, Hong Kong			
2.	Model identifier	A30A3M25			TEXT
3.	Energy efficiency class for standard Dynamic Range (SDR)	F			
4.	On mode power demand in Standard Dynamic Range (SDR)	25.0			W
5.	Energy efficiency class (HDR)	n.a.			
6.	On mode power demand in High Dynamic Range (HDR), if implemented	n.a.			W
7.	Off mode, power demand, if applicable	0.3			W
8.	Standby mode power demand, if applicable	0.5			W
9.	Networked standby mode power demand, if applicable	n.a.			W
10.	Electronic display category	monitor			
11.	Size ratio	21	:	9	integer
12.	Screen resolution	2560	x	1080	pixels
13.	Screen diagonal	74.9			cm
14.	Screen diagonal	29.5			inches
15.	Visible screen area	20.1			dm ²
16.	Panel technology used	LCD			
17.	Automatic Brightness Control (ABC) available	NO			
18.	Voice recognition sensor available	NO			
19.	Room presence sensor available	NO			
20.	Image refresh frequency rate (default)	200			Hz
21.	Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market)	8			Years
22.	Minimum guaranteed availability of spare parts (from the date of end of the placement on the market)	7			Years
23.	Minimum guaranteed product support	7			Years
	Minimum duration of the general guarantee offered by the supplier	5			Years
24.	Power supply type	external			
25.	External power supply (non-standardised and included in the product box)				
	i	GQ48-120400-E1			TEXT
	ii	Input voltage	100-240		V
	iii	Output voltage	12.0		V

Remark: The model number can be replaced by other models in this report.