

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2013 with regard to energy labelling of electronic displays

| | Parameter | Parameter or value and precision | Unit | | |
|-----|--|--|------|-----------------|--------|
| 1. | Supplier's name or trademark. | GIGABYTE | | | |
| | Supplier's address. | G.B.T. Technology Trading GmbH, Am Stadtrand 63, 22047 Hamburg, DE | | | |
| 2. | Model identifier | M32UC | | | |
| 3. | Energy Efficiency Class for Standard Dynamic Range (SDR) | F | | | |
| 4. | On mode power demand in SDR | 33,0 | W | | |
| 5. | Energy Efficiency Class for High Dynamic Range (HDR) | G | | | |
| 6. | On mode power demand in HDR, if implemented | 86,0 | W | | |
| 7. | Off mode, power demand, if applicable | 0,3 | W | | |
| 8. | Standby mode power demand, if applicable | n.a. | W | | |
| 9. | Networked standby mode power demand, if applicable | n.a. | W | | |
| 10. | Electronic display category | Monitor | | | |
| 11. | Size ratio | 16 | : | 9 | |
| 12. | Screen resolution | 3 840 | x | 2 160 | pixels |
| 13. | Screen diagonal | 80,0 | | cm | |
| 14. | Screen diagonal | 32 | | inches | |
| 15. | Visible screen area | 27,3 | | dm ² | |
| 16. | Panel technology used | LED LCD | | | |
| 17. | Automatic Brightness Control (ABC) available | No | | | |
| 18. | Voice recognition sensor available | No | | | |
| 19. | Room presence sensor available | No | | | |
| 20. | Image refresh frequency rate (default) | 60 | | Hz | |
| 21. | Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market) | 8 | | Years | |
| 22. | Minimum guaranteed availability of spare parts (from the date of end of the placement on the market) | 7 | | Years | |
| 23. | Minimum guaranteed product support | 7 | | Years | |
| | Minimum duration of the general guarantee offered by the supplier | 3 | | Years | |
| 24. | Power supply type | External | | | |
| 25. | External power supply (non standardized and included in the product box) | | | | |
| | <i>i</i> | Asian Power Devices Inc. DA-150E19 | | | |
| | <i>ii</i> | Input voltage | 240 | V | |

| | | | | |
|-----|---|--------------------------------------|------|----|
| | <i>iii</i> | Output voltage | 19,0 | V |
| 26. | External standardised power supply (or suitable one if not included in the product box) | | | |
| | <i>i</i> | - | | |
| | <i>ii</i> | Required output voltage | - | V |
| | <i>iii</i> | Required delivered current (minimum) | - | A |
| | <i>iv</i> | Required current frequency | - | Hz |