## Product fiche pursuant to Delegated Regulation (EU) no. 65/2014

Domestic Range Hoods	Answer
Supplier's Name or Trade Mark	HISENSE
Model	CH6T14BBUK
Annual Energy Consumption (AEC hood) in kWh/a	44
- m	
Energy efficiency class	Α
Fluid Dynamic Efficiency (FDE)	30.80%
Find Dynamic Efficiency (FDE)	30.80%
Fluid Dynamic Efficiency (FDE) class	Α
Traid By Harrice Efficiency (192) class	
Lighting Efficiency (LE hood) in lux/Watt	33.3
Lighting efficiency class	Α
Grease Filtering Efficiency	66.10%
Grease Filtering Efficiency class	D
Air flow (in m 3 /h) at minimum and maximum speed in normal use, intensive or boost excluded	378
If available the air flow (in m3/h) at intensive or boost setting	594
	F.C.
Airborne acoustical A-weighted sound power emissions (dB(A)) at minimum and maximum speed	56
available in normal use	
Airborne acoustical A-weighted sound power emissions (dB(A)) at intensive or boost setting	68
All bottle acoustical A-weighted sound power emissions (ub(A)) at intensive or boost setting	00
Power consumption in off mode (P o), in Watt	-
Power consumption in standby mode (P o), in Watt	0.29

Units
kWh per year
Kivii pei yeui
lux/W
iux/ vv
m3/h
m3/h
dB(A)
dB(A)
W
W
W