Product fiche pursuant to Delegated Regulation (EU) no. 65/2014

Domestic Range Hoods	Answer
Supplier's Name or Trade Mark	Belling
Model	BEL FARMHOUSE 90 CHIM
	CRM
	CO 1 M/L /
Annual Energy Consumption (AEC hood) in kWh/a	69 kWh/a
Energy efficiency class	D
Fluid Dynamic Efficiency (FDE)	7.6
Fluid Dynamic Efficiency (FDE) class	F
Lighting Efficiency (LE hood) in lux/Watt	64.3
	•
Lighting efficiency class	A
Grease Filtering Efficiency	90.4
	50.1
Grease Filtering Efficiency class	В
Air flow (in m 3 /h) at minimum and maximum speed in normal use, intensive or boost excluded	311.2/512.1 m3/h
If a well-ble the sin flaws (in we2.4b) at intervalue, and a set setting	21/2
If available the air flow (in m3/h) at intensive or boost setting	N/A
Airborne acoustical A-weighted sound power emissions (dB(A)) at minimum and maximum speed	53/60 dB(A)
available in normal use	55/00 db(A)
Airborne acoustical A-weighted sound power emissions (dB(A)) at intensive or boost setting	N/A
Power consumption in off mode (P o), in Watt	0W
Device construction is standly mode (D, c) is $M(c)$	
Power consumption in standby mode (P o), in Watt	N/A