## Product fiche pursuant to Delegated Regulation (EU) no. 65/2014

Domestic Range Hoods	Answer	Units
Supplier's Name or Trade Mark	Belling	
Model	BEL CHIM 603PYR	
Annual Energy Consumption (AEC hood) in kWh/a	79.4	kWh per year
Energy efficiency class	C	
Life gy efficiency class	C	
Fluid Dynamic Efficiency (FDE)	18.2	
Fluid Dynamic Efficiency (FDE) class	С	
Lighting Efficiency (LE hood) in lux/Watt		lux/W
Lighting efficiency class	С	
Conses Filhadian Filiation	75.4	
Grease Filtering Efficiency	75.1	
Grease Filtering Efficiency class	С	
Grease Therm's Emolency class		
Air flow (in m 3 /h) at minimum and maximum speed in normal use, intensive or boost excluded	260 - 600	m3/h
If available the air flow (in m3/h) at intensive or boost setting		m3/h
Airborne acoustical A-weighted sound power emissions (dB(A)) at minimum and maximum speed	45 - 63	dB(A)
available in normal use		
Airborne acoustical A-weighted sound power emissions (dB(A)) at intensive or boost setting		dB(A)
All bothe acoustical A-weighted sound power emissions (ub(A)) at intensive or boost setting		UD(A)
Power consumption in off mode (P o), in Watt	0	W
Power consumption in standby mode (P o), in Watt	0.49	W